

USA

Dust Guard



26" High Torque Grinder

120 V Direct Drive – Low Amp Draw

Dual Voltage - Switch from 14.9 Amp Draw to 240 Volt

Grind ! Scarify ! Coating Removal ! Polish

Division of Scott Electric • 412-605-2992

Dual Motor, Low Amp Draw, USA Made Grinder with (2) 13" Diamond Driver Plates — High Production, Easy Handling / *Low Fatigue* — for Concrete & Stone Floors.

Cover 26" per pass from a 120 volt 20 amp circuit. A USA engineered AC 120-240V 50/60 Hz motors (2) that easily converts *in the field* from 120 to 240 volt.

Grind, Polish, Coating & Sealer Removal, Scarify and Deep Cleaning Concrete, Stone and other hard surfaces. Finish within 1/2" of walls. Use the dual forward and reverse plate driver switch to navigate irregular surfaces and obstacles with ease.

Two-Piece Design: Handle-body assemble easily separates from the dual motor head for transporting in hard to reach locations such as basements or mezzanines.

Includes (2) 13" Diamond Driver Plates to Grind Concrete, Remove / Coatings, Scarify Concrete and Polish Concrete.

[Click here for plate & tooling info.](#)

26" GRINDER - USA ENGINEERED DESIGN

- Control center is front & center to the operator
- Floating heads - ensures the tooling grinds or scrapes flat and fast, follows the floor's contour, prevents dig and ring marks
- Powered by USA Made TEFC (Totally Enclosed Fan Cooled) Motors - motor is protected from dust, debris and slurry
- 11:1 *Direct Drive* Gear Ratio - torque to drive scrapers & metal diamonds
- 3-position handle for transport, operation and storage
- 120 lumen LED lights (2-Sides, 2-Forward) ! 2" x 10" grooved non-marking transport wheels
- Detachable handle-carriage for transport ! Dual AC-TEFC Motors with 11:1 XHD gears
- Removable collar weights ! Built-in dust control with 2" exhaust port.



Specifications: GP26 w 13" Diamond Drivers (2) – \$4,450.00

Model	G26
Machine Size	26"
Pad Size / Speed	13" x 2 / 165 RPM
Coupler	Steel - not fiberglass which breaks
Max Amp Draw / Weight	14.9 Amp / 348 lbs.
Warranty	1-Year
Motor (2)	1.0 HP, 180 frame TEFC Dual Capacitor AC
Power	120 - 240V, 60 Hz power
Power Cord	50 ft 2-pc (12-3) SJTOW w/ Yellow Twist Lock Plug
Drive System	Triple-XHD 11:1 Helical-Cut Industrial Gears



Carriage mounts with lock pins for easy removal.



Finish to within 1/2" of walls.



Counter-Rotating Tools / Drivers.



Diamonds, PCD's, carbide scrapers - easy mount.